

JAVES 250XL & 350XL

**3LCD projector best performance
for education & business**



Cyber & Stylistic design

4:3 & 16:9 switchable

XGA(1024 X 768) native resolution

Comprehensive input & outputs

Available 2500 & 3500 ANSI lumens



Specification:

Model	AMT-250XL	AMT-350XL
Native resolution	XGA(1024 X 768)	
Display technology	3LCD 0.63"	
Brightness	2500 lm	3500lm
Contra ratio	500:1	
Uniformity	80%	
Lamp	230w NSH 3000hrs (4000hrs @ economical model)	
Noise level	<34dBA[Normal], <29dBA[Eco]	
Projection mode	Front / Rear / Ceiling	
Input	S-video, Composite Video, Video, 15-pin, D-sub x 2, Mini Jack(stereo), RCA(L/R)Audio input	
Output	15-pin D-sub, RS-232, Mini-Jack(Audio Output), RJ45	
Computer compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA, Mac	
Video compatibility	PAL, SECAM, NTSC4.43, PAL-M, N, HDTV(480i, 480p, 575i, 575p, 720p, 1035i, 1080i)	
Aspect ratio	4:3 & 16:9	
Projection lens	F: 2.3 ~ 2.5, 1.2 X optical zoom,	F: 1.58 ~ 1.75
	f=18.82 ~ 22.60mm	1.2 X optical zoom,
	1/4 ~ 16 Digital zoom function	f=18.82 ~ 22.63mm
Throw ratio	Vertical ±30° automatic keystone correction	
Projection distance	70"@2.07m 1.4 ~ 12.7m	
Image size	40" ~ 300"	
H-Synch & V-Synch range	15 ~ 100KHz & 50 ~ 100Hz	
Power consumption	280W	310W
Power supply	100 ~ 240V AC	
Speaker	Single track with 7W	
Operating temperature	0 ~ 40°C	
Store temperature	-10 ~ 60°C	
Standard accessories	User guide, AC power cord, Remote control & Battery, VGA cable, Lens cover, PIN label	
Dimension	345 x 245 x 94mm	
Weight	3.2kg	

Specification subject to Change without prior notice



Room 207, Block B, Seaview Estate, Watson Road, North Point, HONG KONG.

Tel: (852) 2887 5151

Fax: (852) 2503 1144

E-mail: [www.javesprojector](http://www.javesprojector.com)