



# D-7 Series

## Multi-media DLP Projector

**NEW! Vivitek's "Vivid Wheel" brings vivid, true and natural color**  
**Off-n-Go Advanced Cooling System**  
**Easy to carry with handgrip detect, Plug-n-Project**  
**Market leading Tri-mode image brightness adjustment**  
**Password Setting**  
**10 Seconds power off**  
**RoHS & WEEE Certified**

Model	D732MX	D740MX
Display Technology	0.7" 12° DDR DLP	
Brightness	3500 ANSI lumens	4000 ANSI lumens
Resolution	XGA (1024 x 768) Native Support to SXGA+ (1440 x 1050)	
Contrast Ratio	2100 : 1	
Throw Ratio	1.8 ~ 2.1	
Projection Lens	Manual Zoom 26.9mm ~ 29.84mm	Manual Zoom 26.01mm ~ 29.84mm
Projection Lamp	200w OSRAM	280w OSRAM
Uniformity	85%	
Projection Screen Size	23.4" ~ 300"	
Display Aspect Ratio	4 : 3 (Natural) & 16 : 9	
Keystone Correction	+/- 15° (Vertical)	
Computer Singal Compatibility	IBM PC or Compatible (VGA, SVGA, XGA)	
Video Singal Compatibility	SDTV, EDTV, HDTV NTSC / PAL / SECAM	
Computer Singal I/O	Input: DVI-D x 1, D-Sub (RGB) x 1 Output: D-Sub (RGB) x 1	
Video Singal I/O	Input: Composite Video RCA x 1, S-Video x 1	
Audio Singal I/O	Input: Stereo mini-jack x 1, Stereo RCA L&R x 1 Output: Audio x 1	
Built-in Speaker	3w mono speaker x 1	
Control Singal I/O	Input: USB x 1	
Fan Noise	33 dB(STD)	
Security	Kensington Lock	
Dimensions	300mm x 244mm x 88mm	
Weight	7.3 lbs / 3.3 Kg	

### Input Ports Panel



Powered by DLP Technology



RoHS & WEEE Compliant